

Features (Last Rev. July 8, 2007)	'75 Std.	'76 Std.	'76-LTD	'77 Std.	'78 Std.	'79 Std.	'80 Std.	'80 Int.	'81 Std.	'81 Int.	'82 Std.	'82 Int.
<b>GL-1000</b> (Engine 4-Cyl. 0999cc Liquid-Cooled)	Yes	Yes	Yes	Yes	Yes	Yes	----	----	----	----	----	----
GL-1000 - Government rated <b>84 Max.hp</b>	Yes	Yes	Yes	Yes	Yes	Yes	----	----	----	----	----	----
<b>GL-1100</b> (Engine 4-Cyl. 1085cc Liquid-Cooled)	----	----	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes
GL-1100 - Government rated <b>81 Max.hp</b>	----	----	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes
<b>GL-1200</b> (Engine 4-Cyl. 1182cc Liquid-Cooled)	----	----	----	----	----	----	----	----	----	----	----	----
GL-1200 - Government rated <b>86 Max.hp</b>	----	----	----	----	----	----	----	----	----	----	----	----
<b>GL-1500</b> (Engine 6-Cyl. 1520cc Liquid-Cooled)	----	----	----	----	----	----	----	----	----	----	----	----
GL-1500 - Government Max.rating ( <b>per model</b> )	----	----	----	----	----	----	----	----	----	----	----	----
Air Compressor (on-board)	----	----	----	----	----	----	----	----	----	----	----	Optional
Audio System: <b>Clarion II</b> (AM/FM-Intercom)	None	None	None	None	None	None	None	Clarion-II	None	Clarion-II	----	C,Type-II-O
Automatic Hydraulic Valve Adjusters	----	----	----	----	----	----	----	----	----	----	----	----
CB radio (Opt. or Std.)	----	----	----	----	----	----	----	Opt.	----	Opt.	----	Opt.
Brakes: Front, Dual-disc, single piston caliper	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	----	----
Brakes: Front, Dual-disc, twin piston caliper	----	----	----	----	----	----	----	----	----	----	Yes	Yes
Brakes: Integrated <b>F</b> .Dual-disc, <b>Rear</b> Single-disc	----	----	----	----	----	----	----	----	----	----	----	----
Brakes: Rear, Single-disc, single piston caliper	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	----	----
Brakes: Rear, Single-disc, twin piston caliper	----	----	----	----	----	----	----	----	----	----	Yes	Yes
Carburetion (2) 36mm CV	----	----	----	----	----	----	----	----	----	----	----	----
Carburetion (4) 30mm CV	----	----	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes
Carburetion (4) 31mm CV	----	----	----	Yes	Yes	Yes	----	----	----	----	----	----
Carburetion (4) 32mm CV	Yes	Yes	Yes	----	----	----	----	----	----	----	----	----
Electronic <b>Cruise Control</b>	----	----	----	----	----	----	----	----	----	----	----	----
Fuel Capacity	5.0 gal.	5.0 gal.	5.0 gal.	5.0 gal.	5.0 gal.	5.0 gal.	5.3 gal.	5.3 gal.	5.3 gal.	5.3 gal.	5.3 gal.	5.3 gal.
Fuel Injection ( <b>'85 LTD-E and '86 SE-i only</b> )	----	----	----	----	----	----	----	----	----	----	----	----
Trans. Primary reduction	1.708	1.708	1.708	1.708	1.708	1.708	1.708	1.708	1.708	1.708	1.708	1.708
Trans. Secondary reduction	0.825	0.825	0.825	0.825	0.825	0.825	0.973	0.973	0.973	0.973	0.973	0.973
Gear ratio of 1st	2.500	2.500	2.500	2.500	2.500	2.500	2.500	2.500	2.500	2.500	2.500	2.500
Gear ratio of 2nd	1.708	1.708	1.708	1.708	1.708	1.708	1.667	1.667	1.667	1.667	1.667	1.667
Gear ratio of 3rd	1.333	1.333	1.333	1.333	1.333	1.333	1.286	1.286	1.286	1.286	1.250	1.250
Gear ratio of 4th	1.097	1.097	1.097	1.097	1.097	1.097	1.065	1.065	1.065	1.065	1.000	1.000
Gear ratio of 5th	0.939	0.939	0.939	0.939	0.939	0.939	0.909	0.909	0.909	0.909	0.829	0.829
Gear ratio of Final Drive	3.400	3.400	3.400	3.400	3.400	3.400	3.091	3.091	3.091	3.091	3.100	3.100
<b>Ignition System:</b> Electronic (no points)	----	----	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes
<b>Ignition System:</b> Points and Condenser	Yes	Yes	Yes	Yes	Yes	Yes	----	----	----	----	----	----
Instrument Cluster	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog
Saddlebag liners	----	----	----	----	----	----	----	Yes	----	Yes	----	Yes
Saddlebags, Fairing and Trunk	----	----	----	----	----	----	----	Yes	----	Yes	----	Yes
Seat Height	31.9"	31.9"	31.9"	31.9"	31.9"	31.9"	31.3"	31.3"	31.3"	31.3"	31.1"	31.1"
Starting: Elec. <b>ONLY</b>	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Starting: Elec. plus <b>KICK START</b>	Yes	Yes	Yes	Yes	----	----	----	----	----	----	----	----
Tire Size: Front (tubeless)	----	----	----	----	----	----	110/90-19 62H 110/90-19 62H 110/90-19 62H 110/90-19 62H 120/90-18 65H 120/90-18 65					

Features (Last Rev. July 8, 2007)	'75 Std.	'76 Std.	'76-LTD	'77 Std.	'78 Std.	'79 Std.	'80 Std.	'80 Int.	'81 Std.	'81 Int.	'82 Std.	'82 Int.
Tire Size: Front (tube type)	3.50 H-19	3.50 H-19	3.50 H-19	3.50 H-19	3.50 H-19	3.50 H-19	----	----	----	----	----	----
Tire Size: Rear (tube type)	4.50 H-17A	4.50 H-17A	4.50 H-17A	4.50 H-17A	4.50 H-17A	4.50 H-17A	----	----	----	----	----	----
Transmission: 5-Speed, shaft drive	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Transmission: 5-Speed, shaft drive + Reverse	----	----	----	----	----	----	----	----	----	----	----	----
Trunk liners	----	----	----	----	----	----	----	Yes	----	Yes	----	----
Trunk: removeable	----	----	----	----	----	----	----	Yes	----	Yes	----	Yes
Weight - Dry (with no liquids)	584.0 lbs	583.0 lbs	583.0 lbs	595.0 lbs	601.0 lbs	604.0 lbs	586.0 lbs	672.5 lbs	588.7 lbs	672.5 lbs	595.4 lbs	679.1 lbs
Wheels: 10 Cast Web Spokes	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: 11 Cast Spokes	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: 16" front	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: ComStar black reverse	----	----	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes
Wheels: ComStar maintenance free	----	----	----	----	Yes	Yes	----	----	----	----	----	----
Wheels: Wire Spokes	Yes	Yes	Yes	Yes	----	----	----	----	----	----	----	----
Windshield, Adjustable	----	----	----	----	----	----	----	Yes	----	Yes	----	Yes

Features (Last Rev. July 8, 2007)	'82 Asp.	'83 Std.	'83 Int.	'83 Asp.	'84 Std.	'84 Int.	'84 Asp.	'85 Int.	'85 Asp.	'85 Ltd-E	'86 Int.	'86 Asp.
<b>GL-1000</b> (Engine 4-Cyl. 0999cc Liquid-Cooled)	----	----	----	----	----	----	----	----	----	----	----	----
GL-1000 - Government rated <b>84 Max.hp</b>	----	----	----	----	----	----	----	----	----	----	----	----
<b>GL-1100</b> (Engine 4-Cyl. 1085cc Liquid-Cooled)	Yes	Yes	Yes	Yes	----	----	----	----	----	----	----	----
GL-1100 - Government rated <b>81 Max.hp</b>	Yes	Yes	Yes	Yes	----	----	----	----	----	----	----	----
<b>GL-1200</b> (Engine 4-Cyl. 1182cc Liquid-Cooled)	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
GL-1200 - Government rated <b>86 Max.hp</b>	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>GL-1500</b> (Engine 6-Cyl. 1520cc Liquid-Cooled)	----	----	----	----	----	----	----	----	----	----	----	----
GL-1500 - Government Max.rating ( <b>per model</b> )	----	----	----	----	----	----	----	----	----	----	----	----
Air Compressor (on-board)	Yes	----	Optional	Yes	----	----	Yes	----	Yes	Yes	Opt.	Yes
Audio System: <b>Clarion II</b> (AM/FM-Intercom)	C,Type-II	----	C,Type-III-O	C,Type-III	----	P,Type-II	P,Type-III	P,Type-III	P,Type-II	P,Type-III	P,Type-II	P,Type-III
Automatic Hydraulic Valve Adjusters	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
CB radio (Opt. or Std.)	Opt.	----	Opt.	Opt.	----	Opt.	Opt.	----	Opt.	Opt.	----	Opt.
Brakes: Front, Dual-disc, single piston caliper	----	----	----	----	----	----	----	----	----	----	----	----
Brakes: Front, Dual-disc, twin piston caliper	Vented	Yes	Yes	Vented	Yes	Yes	Vented	Yes	Yes	Yes	Vented	Vented
Brakes: Integrated <b>F</b> .Dual-disc, <b>Rear</b> Single-disc	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Brakes: Rear, Single-disc, single piston caliper	----	----	----	----	----	----	----	----	----	----	----	----
Brakes: Rear, Single-disc, twin piston caliper	Vented	Yes	Yes	Vented	Yes	Yes	Vented	Yes	Yes	Yes	Vented	Vented
Carburetion (2) 36mm CV	----	----	----	----	----	----	----	----	----	----	----	----
Carburetion (4) 30mm CV	Yes	Yes	Yes	Yes	----	----	----	----	----	----	----	----
Carburetion (4) 31mm CV	----	----	----	----	----	----	----	----	----	----	----	----
Carburetion (4) 32mm CV	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Electronic <b>Cruise Control</b>	----	----	----	----	----	----	----	----	----	Yes	----	----
Fuel Capacity	5.3 gal.	5.3 gal.	5.3 gal.	5.3 gal.	5.8 gal.	5.8 gal.	5.8 gal.	5.8 gal.	5.8 gal.	5.8 gal.	5.8 gal.	5.8 gal.
Fuel Injection ( <b>'85 LTD-E and '86 SE-i only</b> )	----	----	----	----	----	----	----	----	----	Yes	----	----
Trans. Primary reduction	1.708	1.708	1.708	1.708	1.708	1.708	1.708	1.708	1.708	1.708	1.708	1.708
Trans. Secondary reduction	0.973	0.897	0.897	0.897	0.897	0.897	0.897	0.973	0.973	0.973	0.973	0.973
Gear ratio of 1st	2.500	2.642	2.642	2.642	2.643	2.643	2.643	2.571	2.571	2.571	2.571	2.571
Gear ratio of 2nd	1.667	1.667	1.667	1.667	1.667	1.667	1.667	1.667	1.667	1.667	1.667	1.667
Gear ratio of 3rd	1.250	1.250	1.250	1.250	1.250	1.250	1.250	1.250	1.250	1.250	1.250	1.250
Gear ratio of 4th	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Gear ratio of 5th	0.829	0.829	0.829	0.829	0.829	0.829	0.829	0.800	0.800	0.800	0.800	0.800
Gear ratio of Final Drive	3.100	3.100	3.100	3.100	2.833	2.833	2.833	2.833	2.833	2.833	2.833	2.833
<b>Ignition System:</b> Electronic (no points)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Ignition System:</b> Points and Condenser	----	----	----	----	----	----	----	----	----	----	----	----
Instrument Cluster	2-Analog	2-Analog	2-Analog	Digital	2-Analog	2-Analog	Digital	2-Analog	Digital	Digital	2-Analog	Digital
Saddlebag liners	Yes	----	Yes	Yes	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Saddlebags, Fairing and Trunk	Yes	----	Yes	Yes	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Seat Height	30.7"	30.7"	30.7"	30.7"	30.7"	30.7"	30.7"	30.7"	30.7"	30.7"	30.7"	30.7"
Starting: Elec. <b>ONLY</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Starting: Elec. plus <b>KICK START</b>	----	----	----	----	----	----	----	----	----	----	----	----
Tire Size: Front (tubeless)	120/90-18 65H	120/90-18 65H	120/90-18 65H	120/90-18 65H	130/90-16 67H	130/90-16 67H	130/90-16 67H	130/90-16 67H	130/90-16 67H	130/90-16 67H	130/90-16 67H	130/90-16 67H
Tire Size: Rear (tubeless)	140/90-16 71H	140/90-16 71H	140/90-16 71H	140/90-16 71H	150/90-15 74H	150/90-15 74H	150/90-15 74H	150/90-15 74H	150/90-15 74H	150/90-15 74H	150/90-15 74H	150/90-15 74H

Features (Last Rev. July 8, 2007)	'82 Asp.	'83 Std.	'83 Int.	'83 Asp.	'84 Std.	'84 Int.	'84 Asp.	'85 Int..	'85 Asp.	'85 Ltd-E	'86 Int.	'86 Asp.
Tire Size: Front (tube type)	----	----	----	----	----	----	----	----	----	----	----	----
Tire Size: Rear (tube type)	----	----	----	----	----	----	----	----	----	----	----	----
Transmission: 5-Speed, shaft drive	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Transmission: 5-Speed, shaft drive + <b>Reverse</b>	----	----	----	----	----	----	----	----	----	----	----	----
Trunk liners	----	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Trunk: removeable	Yes	----	Yes	Yes	----	----	----	----	----	----	----	----
Weight - Dry (with no liquids)	702.3 lbs	599.8 lbs	685.8 lbs	707.8 lbs	599.8 lbs	701.2 lbs	723.3 lbs	699.0 lbs	727.7 lbs	771.8 lbs	699.0 lbs	727.7 lbs
Wheels: 10 Cast Web Spokes	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: 11 Cast Spokes	----	Yes	Yes	Yes	----	----	----	----	----	----	----	----
Wheels: 16" front	----	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Wheels: ComStar black reverse	Yes	----	----	----	----	----	----	----	----	----	----	----
Wheels: ComStar maintenance free	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: Wire Spokes	----	----	----	----	----	----	----	----	----	----	----	----
Windshield, Adjustable	Yes	----	Yes	Yes	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Features (Last Rev. July 8, 2007)	'86 SE-i	'87 Int.	'87 Asp.	'88 Std.	'89 Std.	'90 Std.	'90 SE	'91 Int.	'91 Asp.	'91 SE	'92 Int.	'92 Asp.
<b>GL-1000</b> (Engine 4-Cyl. 0999cc Liquid-Cooled)	----	----	----	----	----	----	----	----	----	----	----	----
GL-1000 - Government rated <b>84 Max.hp</b>	----	----	----	----	----	----	----	----	----	----	----	----
<b>GL-1100</b> (Engine 4-Cyl. 1085cc Liquid-Cooled)	----	----	----	----	----	----	----	----	----	----	----	----
GL-1100 - Government rated <b>81 Max.hp</b>	----	----	----	----	----	----	----	----	----	----	----	----
<b>GL-1200</b> (Engine 4-Cyl. 1182cc Liquid-Cooled)	Yes	Yes	Yes	----	----	----	----	----	----	----	----	----
GL-1200 - Government rated <b>86 Max.hp</b>	Yes	Yes	Yes	----	----	----	----	----	----	----	----	----
<b>GL-1500</b> (Engine 6-Cyl. 1520cc Liquid-Cooled)	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
GL-1500 - Government Max.rating ( <b>per model</b> )	----	----	----	96hp	95.8hp	95.8hp	95.8hp	95.2hp	95.8hp	95.8hp	95.2hp	95.2hp
Air Compressor (on-board)	Yes	Opt.	Yes	Yes	Yes	Yes	Yes	----	Yes	Yes	----	Yes
Audio System: <b>Clarion II</b> (AM/FM-Intercom)	P,Type-III	P,Type-II	P,Type-III	H-Type-III	H-Type-III	H-Type-III	H-Type-III	H-Type-III	H-Type-III	H-Type-III	Type-I	H-Type-III
Automatic Hydraulic Valve Adjusters	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
CB radio (Opt. or Std.)	Opt.	----	Opt.	Opt.	Opt.	----	Opt.	----	Opt.	Opt.	----	Opt.
Brakes: Front, Dual-disc, single piston caliper	----	----	----	----	----	----	----	----	----	----	----	----
Brakes: Front, Dual-disc, twin piston caliper	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented
Brakes: Integrated <b>F.</b> Dual-disc, <b>Rear</b> Single-disc	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Brakes: Rear, Single-disc, single piston caliper	----	----	----	----	----	----	----	----	----	----	----	----
Brakes: Rear, Single-disc, twin piston caliper	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented
Carburetion (2) 36mm CV	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Carburetion (4) 30mm CV	----	----	----	----	----	----	----	----	----	----	----	----
Carburetion (4) 31mm CV	----	----	----	----	----	----	----	----	----	----	----	----
Carburetion (4) 32mm CV	Yes	Yes	Yes	----	----	----	----	----	----	----	----	----
Electronic <b>Cruise Control</b>	Yes	----	Yes	Yes	Yes	Yes	Yes	----	Yes	Yes	----	Yes
Fuel Capacity	5.8 gal.	5.8 gal.	5.8 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.
Fuel Injection ( <b>'85 LTD-E and '86 SE-i only</b> )	Yes	----	----	----	----	----	----	----	----	----	----	----
Trans. Primary reduction	1.708	1.708	1.708	1.592	1.592	1.592	1.592	1.592	1.592	1.592	1.592	1.592
Trans. Secondary reduction	0.973	0.973	0.973	0.971	0.971	0.971	0.971	0.971	0.971	0.971	0.971	0.971
Gear ratio of 1st	2.571	2.571	2.571	2.667	2.667	2.667	2.667	2.667	2.667	2.667	2.667	2.667
Gear ratio of 2nd	1.667	1.667	1.667	1.722	1.722	1.722	1.722	1.722	1.722	1.722	1.722	1.722
Gear ratio of 3rd	1.250	1.250	1.250	1.273	1.273	1.273	1.273	1.273	1.273	1.273	1.273	1.273
Gear ratio of 4th	1.000	1.000	1.000	0.964	0.964	0.964	0.964	0.964	0.964	0.964	0.964	0.964
Gear ratio of 5th	0.800	0.800	0.800	0.759	0.759	0.759	0.759	0.759	0.759	0.759	0.759	0.759
Gear ratio of Final Drive	2.833	2.833	2.833	2.833	2.833	2.833	2.833	2.833	2.833	2.833	2.833	2.833
<b>Ignition System:</b> Electronic (no points)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Ignition System:</b> Points and Condenser	----	----	----	----	----	----	----	----	----	----	----	----
Instrument Cluster	Digital	2-Analog	Digital	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog
Saddlebag liners	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Opt.	Yes	Yes	----	Yes
Saddlebags, Fairing and Trunk	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Seat Height	30.7"	30.7"	30.7"	30.3"	30.3"	30.3"	30.3"	29.5"	30.3"	30.3"	29.5"	30.3"
Starting: Elec. <b>ONLY</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Starting: Elec. plus <b>KICK START</b>	----	----	----	----	----	----	----	----	----	----	----	----
Tire Size: Front (tubeless)	130/90-16 67H	130/90-16 67H	130/90-16 67H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H
Tire Size: Rear (tubeless)	150/90-15 74H	150/90-15 74H	150/90-15 74H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H

Features (Last Rev. July 8, 2007)	'86 SE-i	'87 Int.	'87 Asp.	'88 Std.	'89 Std.	'90 Std.	'90 SE	'91 Int.	'91 Asp.	'91 SE	'92 Int.	'92 Asp.
Tire Size: Front (tube type)	----	----	----	----	----	----	----	----	----	----	----	----
Tire Size: Rear (tube type)	----	----	----	----	----	----	----	----	----	----	----	----
Transmission: 5-Speed, shaft drive	Yes	Yes	Yes	----	----	----	----	Yes	----	----	Yes	----
Transmission: 5-Speed, shaft drive + <b>Reverse</b>	----	----	----	Yes	Yes	Yes	Yes	----	Yes	Yes	----	Yes
Trunk liners	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Opt.	Yes	Yes	Yes	Yes
Trunk: removeable	----	----	----	----	----	----	----	----	----	----	----	----
Weight - Dry (with no liquids)	771.8 lbs	699.0 lbs	743.1 lbs	793.8 lbs	793.8 lbs	798.0 lbs	804.0 lbs	760.7 lbs	800.4 lbs	809.2 lbs	767.3 lbs	800.4 lbs
Wheels: 10 Cast Web Spokes	----	----	----	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Wheels: 11 Cast Spokes	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: 16" front	Yes	Yes	Yes	----	----	----	----	----	----	----	----	----
Wheels: ComStar black reverse	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: ComStar maintenance free	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: Wire Spokes	----	----	----	----	----	----	----	----	----	----	----	----
Windshield, Adjustable	Yes	----	Yes	Yes	Yes	Yes	Yes	----	Yes	Yes	----	Yes

Features (Last Rev. July 8, 2007)	'92 SE	'93 Int.	'93 Asp.	'93 SE	'94 Int.	'94 Asp.	'94 SE	'95 Int.	'95 Asp.	'95 SE	'96 Int.	'96 Asp.
<b>GL-1000</b> (Engine 4-Cyl. 0999cc Liquid-Cooled)	----	----	----	----	----	----	----	----	----	----	----	----
GL-1000 - Government rated <b>84 Max.hp</b>	----	----	----	----	----	----	----	----	----	----	----	----
<b>GL-1100</b> (Engine 4-Cyl. 1085cc Liquid-Cooled)	----	----	----	----	----	----	----	----	----	----	----	----
GL-1100 - Government rated <b>81 Max.hp</b>	----	----	----	----	----	----	----	----	----	----	----	----
<b>GL-1200</b> (Engine 4-Cyl. 1182cc Liquid-Cooled)	----	----	----	----	----	----	----	----	----	----	----	----
GL-1200 - Government rated <b>86 Max.hp</b>	----	----	----	----	----	----	----	----	----	----	----	----
<b>GL-1500</b> (Engine 6-Cyl. 1520cc Liquid-Cooled)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
GL-1500 - Government Max.rating ( <b>per model</b> )	95.2hp	95.2hp	95.2hp	95.2hp	96hp	96hp	96hp	96hp	96hp	96hp	96hp	96hp
Air Compressor (on-board)	Yes	----	Yes	Yes	----	Yes	Yes	----	Yes	Yes	----	Yes
Audio System: <b>Clarion II</b> (AM/FM-Intercom)	H-Type-III	Type-I	H-Type-III	H-Type-III	Type-I	H-Type-III	H-Type-III	Type-I	H-Type-III	H-Type-III	Type-I	H-Type-III
Automatic Hydraulic Valve Adjusters	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
CB radio (Opt. or Std.)	Opt.	----	Opt.	Std.	----	Opt.	Std.	----	Opt.	Std.	----	Opt.
Brakes: Front, Dual-disc, single piston caliper	----	----	----	----	----	----	----	----	----	----	----	----
Brakes: Front, Dual-disc, twin piston caliper	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented
Brakes: Integrated <b>F.</b> Dual-disc, <b>Rear</b> Single-disc	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Brakes: Rear, Single-disc, single piston caliper	----	----	----	----	----	----	----	----	----	----	----	----
Brakes: Rear, Single-disc, twin piston caliper	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented	Vented
Carburetion (2) 36mm CV	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Carburetion (4) 30mm CV	----	----	----	----	----	----	----	----	----	----	----	----
Carburetion (4) 31mm CV	----	----	----	----	----	----	----	----	----	----	----	----
Carburetion (4) 32mm CV	----	----	----	----	----	----	----	----	----	----	----	----
Electronic <b>Cruise Control</b>	Yes	----	Yes	Yes	----	Yes	Yes	----	Yes	Yes	----	Yes
Fuel Capacity	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	6.3 gal.	----	----
Fuel Injection ( <b>'85 LTD-E and '86 SE-i only</b> )	----	----	----	----	----	----	----	----	----	----	----	----
Trans. Primary reduction	1.592	1.592	1.592	1.592	1.592	1.592	1.592	1.592	1.592	1.592		
Trans. Secondary reduction	0.971	0.971	0.971	0.971	0.971	0.971	0.971	0.971	0.971	0.971		
Gear ratio of 1st	2.667	2.667	2.667	2.667	2.667	2.667	2.667	2.667	2.667	2.667	2.666	2.666
Gear ratio of 2nd	1.722	1.722	1.722	1.722	1.722	1.722	1.722	1.722	1.722	1.722	1.722	1.722
Gear ratio of 3rd	1.273	1.273	1.273	1.273	1.273	1.273	1.273	1.273	1.273	1.273	1.272	1.272
Gear ratio of 4th	0.964	0.964	0.964	0.964	0.964	0.964	0.964	0.964	0.964	0.964	0.964	0.964
Gear ratio of 5th	0.759	0.759	0.759	0.759	0.759	0.759	0.759	0.759	0.759	0.759	0.758	0.758
Gear ratio of Final Drive	2.833	2.833	2.833	2.833	2.833	2.833	2.833	2.833	2.833	2.833	2.833	2.833
<b>Ignition System:</b> Electronic (no points)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Ignition System:</b> Points and Condenser	----	----	----	----	----	----	----	----	----	----	----	----
Instrument Cluster	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog
Saddlebag liners	Yes	----	Yes	Yes	----	Yes	Yes	----	Yes	Yes	----	Yes
Saddlebags, Fairing and Trunk	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Seat Height	30.3"	29.5"	30.3"	30.3"	29.5"	30.3"	30.3"	29.1	29.1	29.1	29.1	29.1
Starting: Elec. <b>ONLY</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Starting: Elec. plus <b>KICK START</b>	----	----	----	----	----	----	----	----	----	----	----	----
Tire Size: Front (tubeless)	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H
Tire Size: Rear (tubeless)	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H

Features (Last Rev. July 8, 2007)	'92 SE	'93 Int.	'93 Asp.	'93 SE	'94 Int.	'94 Asp.	'94 SE	'95 Int.	'95 Asp.	'95 SE	'96 Int.	'96 Asp.
Tire Size: Front (tube type)	----	----	----	----	----	----	----	----	----	----	----	----
Tire Size: Rear (tube type)	----	----	----	----	----	----	----	----	----	----	----	----
Transmission: 5-Speed, shaft drive	----	Yes	----	----	Yes	----	----	Yes	----	----	Yes	----
Transmission: 5-Speed, shaft drive + <b>Reverse</b>	Yes	----	Yes	Yes	----	Yes	Yes	----	Yes	Yes	----	Yes
Trunk liners	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Trunk: removeable	----	----	----	----	----	----	----	----	----	----	----	----
Weight - Dry (with no liquids)	809.2 lbs	767.3 lbs	800.4 lbs	813.0 lbs	767.2 lbs	800.3 lbs	813.5 lbs	769.4 lbs	802.5 lbs	815.7 lbs		
Wheels: 10 Cast Web Spokes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Wheels: 11 Cast Spokes	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: 16" front	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: ComStar black reverse	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: ComStar maintenance free	----	----	----	----	----	----	----	----	----	----	----	----
Wheels: Wire Spokes	----	----	----	----	----	----	----	----	----	----	----	----
Windshield, Adjustable	Yes		Yes	Yes		Yes	Yes		Yes	Yes		Yes



Features (Last Rev. July 8, 2007)	'96 SE	'97 Asp.	'97 SE	'98 Asp.	'98 SE
<b>GL-1000</b> (Engine 4-Cyl. 0999cc Liquid-Cooled)	----	----	----	----	----
GL-1000 - Government rated <b>84 Max.hp</b>	----	----	----	----	----
<b>GL-1100</b> (Engine 4-Cyl. 1085cc Liquid-Cooled)	----	----	----	----	----
GL-1100 - Government rated <b>81 Max.hp</b>	----	----	----	----	----
<b>GL-1200</b> (Engine 4-Cyl. 1182cc Liquid-Cooled)	----	----	----	----	----
GL-1200 - Government rated <b>86 Max.hp</b>	----	----	----	----	----
<b>GL-1500</b> (Engine 6-Cyl. 1520cc Liquid-Cooled)	Yes	Yes	Yes	Yes	Yes
GL-1500 - Government Max.rating ( <b>per model</b> )	96hp	96hp	96hp	96hp	96hp
Air Compressor (on-board)	Yes	Yes	Yes	Yes	Yes
Audio System: <b>Clarion II</b> (AM/FM-Intercom)	H-Type-III	H-Type-III	H-Type-III	H-Type-III	H-Type-III
Automatic Hydraulic Valve Adjusters	Yes		Yes		Yes
CB radio (Opt. or Std.)	Std.	Opt.	Std.	Opt.	Std.
Brakes: Front, Dual-disc, single piston caliper	----	----	----	----	----
Brakes: Front, Dual-disc, twin piston caliper	Vented	Vented	Vented	Vented	Vented
Brakes: Integrated <b>F.</b> Dual-disc, <b>Rear</b> Single-disc	Yes	Yes	Yes	Yes	Yes
Brakes: Rear, Single-disc, single piston caliper	----	----	----	----	----
Brakes: Rear, Single-disc, twin piston caliper	Vented	Vented	Vented	Vented	Vented
Carburetion (2) 36mm CV	Yes	Yes	Yes	Yes	Yes
Carburetion (4) 30mm CV	----	----	----	----	----
Carburetion (4) 31mm CV	----	----	----	----	----
Carburetion (4) 32mm CV	----	----	----	----	----
Electronic <b>Cruise Control</b>	Yes	Yes	Yes	Yes	Yes
Fuel Capacity	----	----	----	----	----
Fuel Injection ( <b>'85 LTD-E and '86 SE-i only</b> )	----	----	----	----	----
Trans. Primary reduction					
Trans. Secondary reduction					
Gear ratio of 1st	2.666	2.666	2.666		
Gear ratio of 2nd	1.722	1.722	1.722		
Gear ratio of 3rd	1.272	1.272	1.272		
Gear ratio of 4th	0.964	0.964	0.964		
Gear ratio of 5th	0.758	0.758	0.758		
Gear ratio of Final Drive	2.833	2.833	2.833		
<b>Ignition System:</b> Electronic (no points)	Yes	Yes	Yes	Yes	Yes
<b>Ignition System:</b> Points and Condenser	----	----	----	----	----
Instrument Cluster	2-Analog	2-Analog	2-Analog	2-Analog	2-Analog
Saddlebag liners	Yes	Yes	Yes	Yes	Yes
Saddlebags, Fairing and Trunk	Yes	Yes	Yes	Yes	Yes
Seat Height	29.1	29.1	29.1		
Starting: Elec. <b>ONLY</b>	Yes	Yes	Yes	Yes	Yes
Starting: Elec. plus <b>KICK START</b>	----	----	----	----	----
Tire Size: Front (tubeless)	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H	130/70-18 63H
Tire Size: Rear (tubeless)	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H	160/80-16 75H

Features (Last Rev. July 8, 2007)	'96 SE	'97 Asp.	'97 SE	'98 Asp.	'98 SE
Tire Size: Front (tube type)	----	----	----	----	----
Tire Size: Rear (tube type)	----	----	----	----	----
Transmission: 5-Speed, shaft drive	----	----	----	----	----
Transmission: 5-Speed, shaft drive + <b>Reverse</b>	Yes	Yes	Yes	Yes	Yes
Trunk liners	Yes	Yes	Yes	Yes	Yes
Trunk: removeable	----	----	----	----	----
Weight - Dry (with no liquids)	816 lbs.				
Wheels: 10 Cast Web Spokes	Yes	Yes	Yes	Yes	Yes
Wheels: 11 Cast Spokes	----	----	----	----	----
Wheels: 16" front	----	----	----	----	----
Wheels: ComStar black reverse	----	----	----	----	----
Wheels: ComStar maintenance free	----	----	----	----	----
Wheels: Wire Spokes	----	----	----	----	----
Windshield, Adjustable	Yes	Yes	Yes	Yes	Yes